

Gov 50: 11. Tidying and Joining Data

Matthew Blackwell

Harvard University

Roadmap

1. Pivoting data longer
2. Joining data sets

1/ Pivoting data longer

Mortality data

```
library(tidyverse)
library(gov50data)
mortality
```

```
## # A tibble: 217 x 52
##   country      country_code indicator `1972` `1973` `1974`
##   <chr>        <chr>      <chr>    <dbl> <dbl> <dbl>
## 1 Aruba        ABW        Mortalit~ NA     NA     NA
## 2 Afghanistan  AFG        Mortalit~ 291   285.   280.
## 3 Angola       AGO        Mortalit~ NA     NA     NA
## 4 Albania      ALB        Mortalit~ NA     NA     NA
## 5 Andorra      AND        Mortalit~ NA     NA     NA
## 6 United Arab ~ ARE        Mortalit~ 80.1  72.6  65.7
## 7 Argentina    ARG        Mortalit~ 69.7  68.2  66.1
## 8 Armenia      ARM        Mortalit~ NA     NA     NA
## 9 American Sam~ ASM        Mortalit~ NA     NA     NA
## 10 Antigua and ~ ATG        Mortalit~ 26.9  25.1  23.5
## # i 207 more rows
## # i 46 more variables: `1975` <dbl>, `1976` <dbl>,
## #   `1977` <dbl>, `1978` <dbl>, `1979` <dbl>, `1980` <dbl>,
## #   `1981` <dbl>, `1982` <dbl>, `1983` <dbl>, `1984` <dbl>,
## #   `1985` <dbl>, `1986` <dbl>, `1987` <dbl>, `1988` <dbl>,
```

Pivoting longer

Mortality data in a “wide” format (years in columns).

We can convert this to country-year rows with `pivot_longer()`.

```
mydata |>
  pivot_longer(
    cols = <<variables to pivot>>,
    names_to = <<new variable to put column names>>,
    values_to = <<new variable to put column values>>
  )
```

Pivoting the mortality data


```
mortality |>
  select(-indicator) |>
  pivot_longer(
    cols = `1972`:`2020`,
    names_to = "year",
    values_to = "child_mortality"
  )
```

```
## # A tibble: 10,633 x 4
##   country country_code year  child_mortality
##   <chr>    <chr>         <chr>         <dbl>
## 1 Aruba    ABW            1972            NA
## 2 Aruba    ABW            1973            NA
## 3 Aruba    ABW            1974            NA
## 4 Aruba    ABW            1975            NA
## 5 Aruba    ABW            1976            NA
## 6 Aruba    ABW            1977            NA
## 7 Aruba    ABW            1978            NA
## 8 Aruba    ABW            1979            NA
## 9 Aruba    ABW            1980            NA
## 10 Aruba   ABW            1981            NA
## # i 10,623 more rows
```

Let's do line plots!

```
mortality |>
  select(-indicator) |>
  pivot_longer(
    cols = `1972`:`2020`,
    names_to = "year",
    values_to = "child_mortality"
  ) |>
  ggplot(mapping = aes(x = year, y = child_mortality, group = country)) +
  geom_line(alpha = 0.25)
```

Hmm, what's going on?



Making sure year is numeric

By default, pivoted column names are characters, but we can transform them:


```
mortality_long <- mortality |>
  select(-indicator) |>
  pivot_longer(
    cols = `1972`:`2020`,
    names_to = "year",
    values_to = "child_mortality"
  ) |>
  mutate(year = as.integer(year))
mortality_long
```

```
## # A tibble: 10,633 x 4
##   country country_code year child_mortality
##   <chr>    <chr>      <int>         <dbl>
## 1 Aruba    ABW          1972            NA
## 2 Aruba    ABW          1973            NA
## 3 Aruba    ABW          1974            NA
## 4 Aruba    ABW          1975            NA
## 5 Aruba    ABW          1976            NA
## 6 Aruba    ABW          1977            NA
```

Let's (re)do line plots!

```
mortality_long |>  
  ggplot(mapping = aes(x = year, y = child_mortality, group = country)) +  
  geom_line(alpha = 0.25)
```

There we go



Spotify data

```
spotify
```

```
## # A tibble: 490 x 54
##   `Track Name`   Artist week1 week2 week3 week4 week5 week6
##   <chr>          <chr> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>
## 1 The Box        Roddy~   1     1     1     1     1     1
## 2 ROXANNE        Arizo~   2     4     5     4     4     4
## 3 Yummy          Justi~   3     6    17    17    17    24
## 4 Circles        Post ~   4     7     9    10     7    10
## 5 BOP            DaBaby   5     5     7     5    11    12
## 6 Falling        Trevo~   6     8    10     7     6     8
## 7 Dance Monkey   Tones~   7    13    13    12    12    13
## 8 Bandit (with ~ Juice~   8    11    14    14    15    20
## 9 Futsal Shuffl~ Lil U~   9     9    19    21    24    32
## 10 everything i ~ Billi~  10    17    28     9     8    11
## # i 480 more rows
## # i 46 more variables: week7 <dbl>, week8 <dbl>,
## #   week9 <dbl>, week10 <dbl>, week11 <dbl>, week12 <dbl>,
## #   week13 <dbl>, week14 <dbl>, week15 <dbl>, week16 <dbl>,
## #   week17 <dbl>, week18 <dbl>, week19 <dbl>, week20 <dbl>,
## #   week21 <dbl>, week22 <dbl>, week23 <dbl>, week24 <dbl>,
## #   week25 <dbl>, week26 <dbl>, week27 <dbl>, ...
```

Pivoting not ideal

Last approach isn't ideal because of the week prefix:

```
spotify |>
  pivot_longer(
    cols = c(`Track Name`, -Artist),
    names_to = "week_of_year",
    values_to = "rank"
  )
```

```
## # A tibble: 25,480 x 4
##   `Track Name` Artist      week_of_year rank
##   <chr>         <chr>         <chr>         <dbl>
## 1 The Box      Roddy Ricch week1           1
## 2 The Box      Roddy Ricch week2           1
## 3 The Box      Roddy Ricch week3           1
## 4 The Box      Roddy Ricch week4           1
## 5 The Box      Roddy Ricch week5           1
## 6 The Box      Roddy Ricch week6           1
## 7 The Box      Roddy Ricch week7           1
## 8 The Box      Roddy Ricch week8           1
## 9 The Box      Roddy Ricch week9           1
## 10 The Box     Roddy Ricch week10          1
```

Removing a column name prefix

When the data in the column name has a fixed prefix, we can use the `names_prefix` to remove it when moving the data to rows

```
spotify |>
  pivot_longer(
    cols = c(-`Track Name`, -Artist),
    names_to = "week_of_year",
    values_to = "rank",
    names_prefix = "week"
  ) |>
  mutate(
    week_of_year = as.integer(week_of_year)
  )
```

Removing a column name prefix

```
## # A tibble: 25,480 x 4
##   `Track Name` Artist      week_of_year rank
##   <chr>         <chr>          <int> <dbl>
## 1 The Box      Roddy Ricch         1     1
## 2 The Box      Roddy Ricch         2     1
## 3 The Box      Roddy Ricch         3     1
## 4 The Box      Roddy Ricch         4     1
## 5 The Box      Roddy Ricch         5     1
## 6 The Box      Roddy Ricch         6     1
## 7 The Box      Roddy Ricch         7     1
## 8 The Box      Roddy Ricch         8     1
## 9 The Box      Roddy Ricch         9     1
## 10 The Box     Roddy Ricch        10     1
## # i 25,470 more rows
```

2/ Joining data sets

Gapminder data

```
library(gapminder)
gapminder
```

```
## # A tibble: 1,704 x 6
##   country      continent  year lifeExp      pop gdpPercap
##   <fct>        <fct>    <int> <dbl>    <int>    <dbl>
## 1 Afghanistan Asia      1952  28.8  8425333  779.
## 2 Afghanistan Asia      1957  30.3  9240934  821.
## 3 Afghanistan Asia      1962  32.0 10267083  853.
## 4 Afghanistan Asia      1967  34.0 11537966  836.
## 5 Afghanistan Asia      1972  36.1 13079460  740.
## 6 Afghanistan Asia      1977  38.4 14880372  786.
## 7 Afghanistan Asia      1982  39.9 12881816  978.
## 8 Afghanistan Asia      1987  40.8 13867957  852.
## 9 Afghanistan Asia      1992  41.7 16317921  649.
## 10 Afghanistan Asia      1997  41.8 22227415  635.
## # i 1,694 more rows
```

Joining data sets

What if we want to add the `child_mortality` variable to the `gampinder` data?

Joining data sets

What if we want to add the `child_mortality` variable to the `gapminder` data?

Just add the columns? Rows are not aligned properly!

```
gapminder |>
  select(country, year) |>
  head()
```

```
## # A tibble: 6 x 2
##   country      year
##   <fct>      <int>
## 1 Afghanistan  1952
## 2 Afghanistan  1957
## 3 Afghanistan  1962
## 4 Afghanistan  1967
## 5 Afghanistan  1972
## 6 Afghanistan  1977
```

```
mortality_long |>
  select(country, year) |>
  head()
```

```
## # A tibble: 6 x 2
##   country      year
##   <chr>      <int>
## 1 Aruba        1972
## 2 Aruba        1973
## 3 Aruba        1974
## 4 Aruba        1975
## 5 Aruba        1976
## 6 Aruba        1977
```

Key variables

A **primary key** is a variable or set of variables that uniquely identifies rows in the data.

- {country, year} in the gapminder data

Key variables

A **primary key** is a variable or set of variables that uniquely identifies rows in the data.

- {country, year} in the gapminder data

A **foreign key** is the corresponding variable(s) in another table.

- {country, year} in the mortality_long data

Key variables

A **primary key** is a variable or set of variables that uniquely identifies rows in the data.

- {country, year} in the gapminder data

A **foreign key** is the corresponding variable(s) in another table.

- {country, year} in the mortality_long data

If we align the two tables based on these variables, we can add variables from one to the other.

Checking that the keys are unique

Things get weird if these keys are not unique. Let's check.

Checking primary key is unique:

```
gapminder |>
  count(country, year) |>
  filter(n > 1)
```

```
## # A tibble: 0 x 3
```

Checking foreign key:

```
mortality_long |>
  count(country, year) |>
  filter(n > 1)
```

```
## # A tibble: 0 x 3
```

left_join(): add variables to primary table

left_join() keeps all rows from the first argument/piped data:

```
gapminder |>
  left_join(mortality_long) |>
  select(country, year, lifeExp, pop, gdpPercap, child_mortality) |>
  head(n = 6)
```

```
## Joining with `by = join_by(country, year)`
```

```
## # A tibble: 6 x 6
```

```
##   country      year lifeExp   pop gdpPercap child_mortality
##   <chr>        <int> <dbl> <int> <dbl>         <dbl>
## 1 Afghanistan  1952   28.8 8.43e6   779.           NA
## 2 Afghanistan  1957   30.3 9.24e6   821.           NA
## 3 Afghanistan  1962   32.0 1.03e7   853.           NA
## 4 Afghanistan  1967   34.0 1.15e7   836.           NA
## 5 Afghanistan  1972   36.1 1.31e7   740.           291
## 6 Afghanistan  1977   38.4 1.49e7   786.           262.
```

Rows in primary table not in foreign table: new values are NA.

inner_join(): add and filter

inner_join() adds the variables from the foreign table and filters to rows in both tables:

```
gapminder |>
  inner_join(mortality_long) |>
  select(country, year, lifeExp, pop, gdpPercap, child_mortality) |>
  head(n = 6)
```

```
## Joining with `by = join_by(country, year)`
```

```
## # A tibble: 6 x 6
```


```
##   country      year lifeExp   pop gdpPercap child_mortality
##   <chr>      <int> <dbl> <int> <dbl>         <dbl>
## 1 Afghanistan 1972   36.1 1.31e7   740.         291
## 2 Afghanistan 1977   38.4 1.49e7   786.         262.
## 3 Afghanistan 1982   39.9 1.29e7   978.         231.
## 4 Afghanistan 1987   40.8 1.39e7   852.         198.
## 5 Afghanistan 1992   41.7 1.63e7   649.         166.
## 6 Afghanistan 1997   41.8 2.22e7   635.         142.
```

How inner joins work

Two data sets:

x		y	
1	x1	1	y1
2	x2	2	y2
3	x3	4	y3

Find matching keys:




How left joins work

Two data sets:

x		y	
1	x1	1	y1
2	x2	2	y2
3	x3	4	y3

Keep all x keys:



More complicated example

```
library(nycflights13)
flights2 <- flights |>
  select(year, time_hour, origin, dest, tailnum, carrier)
flights2
```

```
## # A tibble: 336,776 x 6
```

```
##   year time_hour          origin dest  tailnum carrier
##   <int> <dtm>             <chr> <chr> <chr>   <chr>
## 1  2013 2013-01-01 05:00:00 EWR   IAH   N14228  UA
## 2  2013 2013-01-01 05:00:00 LGA   IAH   N24211  UA
## 3  2013 2013-01-01 05:00:00 JFK   MIA   N619AA  AA
## 4  2013 2013-01-01 05:00:00 JFK   BQN   N804JB  B6
## 5  2013 2013-01-01 06:00:00 LGA   ATL   N668DN  DL
## 6  2013 2013-01-01 05:00:00 EWR   ORD   N39463  UA
## 7  2013 2013-01-01 06:00:00 EWR   FLL   N516JB  B6
## 8  2013 2013-01-01 06:00:00 LGA   IAD   N829AS  EV
## 9  2013 2013-01-01 06:00:00 JFK   MCO   N593JB  B6
## 10 2013 2013-01-01 06:00:00 LGA   ORD   N3ALAA  AA
## # i 336,766 more rows
```

Planes data

```
planes2 <- planes |>
  select(tailnum, year, type, engine, seats)
planes2
```

```
## # A tibble: 3,322 x 5
##   tailnum year type          engine      seats
##   <chr>   <int> <chr>          <chr>      <int>
## 1 N10156  2004 Fixed wing multi engine Turbo-fan    55
## 2 N102UW  1998 Fixed wing multi engine Turbo-fan   182
## 3 N103US  1999 Fixed wing multi engine Turbo-fan   182
## 4 N104UW  1999 Fixed wing multi engine Turbo-fan   182
## 5 N10575  2002 Fixed wing multi engine Turbo-fan    55
## 6 N105UW  1999 Fixed wing multi engine Turbo-fan   182
## 7 N107US  1999 Fixed wing multi engine Turbo-fan   182
## 8 N108UW  1999 Fixed wing multi engine Turbo-fan   182
## 9 N109UW  1999 Fixed wing multi engine Turbo-fan   182
## 10 N110UW  1999 Fixed wing multi engine Turbo-fan   182
## # i 3,312 more rows
```

year here is manufacture year.

What happens with naive join?

```
flights2 |>
  left_join(planes2)
```

```
## Joining with `by = join_by(year, tailnum)`
```

```
## # A tibble: 336,776 x 9
```

```
##   year time_hour      origin dest tailnum carrier type engine
##   <int> <dtm>          <chr> <chr> <chr> <chr> <chr> <chr>
## 1  2013 2013-01-01 05:00:00 EWR   IAH   N14228  UA    <NA> <NA>
## 2  2013 2013-01-01 05:00:00 LGA   IAH   N24211  UA    <NA> <NA>
## 3  2013 2013-01-01 05:00:00 JFK   MIA   N619AA  AA    <NA> <NA>
## 4  2013 2013-01-01 05:00:00 JFK   BQN   N804JB  B6    <NA> <NA>
## 5  2013 2013-01-01 06:00:00 LGA   ATL   N668DN  DL    <NA> <NA>
## 6  2013 2013-01-01 05:00:00 EWR   ORD   N39463  UA    <NA> <NA>
## 7  2013 2013-01-01 06:00:00 EWR   FLL   N516JB  B6    <NA> <NA>
## 8  2013 2013-01-01 06:00:00 LGA   IAD   N829AS  EV    <NA> <NA>
## 9  2013 2013-01-01 06:00:00 JFK   MCO   N593JB  B6    <NA> <NA>
## 10 2013 2013-01-01 06:00:00 LGA   ORD   N3ALAA  AA    <NA> <NA>
## # i 336,766 more rows
## # i 1 more variable: seats <int>
```

Specify the joining variables

```
flights2 |>
  left_join(planes2, by = "tailnum")
```

```
## # A tibble: 336,776 x 10
##   year.x time_hour          origin dest  tailnum carrier year.y
##   <int> <dtm>          <chr> <chr> <chr>   <chr>   <int>
## 1   2013 2013-01-01 05:00:00 EWR   IAH   N14228  UA     1999
## 2   2013 2013-01-01 05:00:00 LGA   IAH   N24211  UA     1998
## 3   2013 2013-01-01 05:00:00 JFK   MIA   N619AA  AA     1990
## 4   2013 2013-01-01 05:00:00 JFK   BQN   N804JB  B6     2012
## 5   2013 2013-01-01 06:00:00 LGA   ATL   N668DN  DL     1991
## 6   2013 2013-01-01 05:00:00 EWR   ORD   N39463  UA     2012
## 7   2013 2013-01-01 06:00:00 EWR   FLL   N516JB  B6     2000
## 8   2013 2013-01-01 06:00:00 LGA   IAD   N829AS  EV     1998
## 9   2013 2013-01-01 06:00:00 JFK   MCO   N593JB  B6     2004
## 10  2013 2013-01-01 06:00:00 LGA   ORD   N3ALAA  AA     NA
## # i 336,766 more rows
## # i 3 more variables: type <chr>, engine <chr>, seats <int>
```

Change variables names

```
flights2 |>
  left_join(planes2 |> rename(manufacture_year = year))

## Joining with `by = join_by(tailnum)`

## # A tibble: 336,776 x 10
##   year time_hour          origin dest  tailnum carrier
##   <int> <dtm>              <chr> <chr> <chr>   <chr>
## 1  2013 2013-01-01 05:00:00 EWR   IAH   N14228  UA
## 2  2013 2013-01-01 05:00:00 LGA   IAH   N24211  UA
## 3  2013 2013-01-01 05:00:00 JFK   MIA   N619AA  AA
## 4  2013 2013-01-01 05:00:00 JFK   BQN   N804JB  B6
## 5  2013 2013-01-01 06:00:00 LGA   ATL   N668DN  DL
## 6  2013 2013-01-01 05:00:00 EWR   ORD   N39463  UA
## 7  2013 2013-01-01 06:00:00 EWR   FLL   N516JB  B6
## 8  2013 2013-01-01 06:00:00 LGA   IAD   N829AS  EV
## 9  2013 2013-01-01 06:00:00 JFK   MCO   N593JB  B6
## 10 2013 2013-01-01 06:00:00 LGA   ORD   N3ALAA  AA
## # i 336,766 more rows
## # i 4 more variables: manufacture_year <int>, type <chr>,
## #   engine <chr>, seats <int>
```